

## FEATURES

### STANDARD



### USED BY:

- BANKS/CREDIT INSTITUTIONS
- CLUBS/ASSOCIATIONS
- DEPARTMENT STORES
- SERVICE BUREAUS

### IDEAL FOR:

- CREDIT/FINANCIAL CARDS
- GIFT CARDS
- PREPAID CARDS
- LOYALTY CARDS

### IN LINE SOLUTIONS:

- E 1000/2000
- T 1000/2000
- C 1000
- CAM 3030
- CAM 8080

### SOFTWARE



# PRO SERIES LABEL DISPENSER 1500



## CARD LABELING SYSTEM

### LET YOUR CARD HOLDERS KNOW YOUR MESSAGE

- ✓ Automatically affixes labels to thermally printed or embossed cards.  
Operates as stand alone or in-line with other Pro Series equipment.



**SINGAPORE:**  
VICCARD PTE LTD  
Email [viccard@singnet.com.sg](mailto:viccard@singnet.com.sg) | Tel: 65-6288 1801  
[www.viccard.com.sg](http://www.viccard.com.sg)

**MALAYSIA**  
VICCARD M SDN BHD  
Email [sales@viccard.com.my](mailto:sales@viccard.com.my) | Tel: 603-7960 7932  
[www.viccard.com.my](http://www.viccard.com.my)

For more information, visit our website

## TECHNICAL FEATURES



Label dispenser

**LABEL DISPENSER 1500**

**MULTICARD 2013**

**POWERCARD INTEGRATION**



**ROHS**

**UL US LISTED**

**CCC CE FC**

### CARD & FEEDING

<b>input hopper</b>	150 pre-embossed cards
<b>output hopper</b>	200 cards
<b>reject hopper</b>	10 cards
<b>card format</b>	CR80 - ISO standard
<b>card thickness</b>	da 0,76 to 0,8mm / 29,92 to 31,5 mil
<b>card materials</b>	ABS, PVC and composite
<b>label dimensions</b>	25 x 75 / 0,984x2,953 in
<b>label position</b>	fixed
<b>label personalization</b>	on request
<b>performance</b>	900 / 1000 CPH (stand alone)

### COMMUNICATION INTERFACE & SOFTWARE

<b>comm. interface</b>	RS232 serial port
<b>operating system</b>	Multicard compatible with Windows XP/Vista/7
<b>application program</b>	User interface monitoring, card production control, automatic card remake option, system status and help messages displayed on Personal Computer.
<b>software application (optional)</b>	PowerCard Integration: The PowerCard Integration software is capable of managing the whole production process, from data import to card mailing, supervising multiple production lines simultaneously and ensuring complete integrity of the production area in real time. PowerCard Integration is the perfect application for production environments where a high throughput and a wide range of jobs are the norm.

### HARDWARE

<b>power supply</b>	100 - 117 - 220 - 230 or 240 Volts - 50 or 60 Hz
<b>operating environment</b>	5°C - 40°C / 41°F to 104°F
<b>dimensions (WxDxH)</b>	860 x 480 x 350 mm / 33.8" x 18.9" x 13.8" in
<b>weight</b>	50 kg / 110 lbs
<b>floor stand</b>	Optional (required for in-line operation)
<b>in-line configuration</b>	The PRO SERIES units can operate stand alone or in-line configuration with 2 up to 5 equipments. The LD1500 can be connected to: E1000/2000, T1000/2000, C1000, CAM3030 e CAM8080

**CONVENIENT & PRACTICAL:** The LD1500 card labeling system adds versatility and practicality to your card issuance programs. It automatically affixes activation labels, special instructions, or any other message you wish your cardholders to receive.