



Card Solutions For A Better World

Model ME1000s/2000s Metal Plate Embosser

ME1000S | ME2000S



TOUCH
SCREEN 7"



INTERNET
OF THINGS



WiFi



USB



ETHERNET



METAL
PLATE
Systems

METAL PLATE EMOSSER

The **ME1000S** and **ME2000S** are robust and reliable electronic embossers engineered for heavy duty and able to handle large metal plate volumes. ME series supports a wide variety of sizes, shapes, thickness including stainless steel, aluminum, copper and brass. With a 10% increase in production speed, a completely renewed design and new features, the **ME1000S** and **ME2000S** are advanced solution that can be integrated into any existing factory or office network.

7" color touchscreen display with high resolution

The **ME1000S** and **ME2000S** is equipped with a built-in 7" WVGA LCD touchscreen display with simple and easy to use icon and buttons. The user can access and manage machine functions through a multi-level menu in an easy and intuitive way.

IoT (Internet of Things) remote access and management

- **Web services:** The machine set-up and operations can be entirely managed remotely via the web or through the use of VNC (Virtual Networking Computing) client, using a personal computer or other devices connected to the Customer's network.
- **Data transfer:** Data import/export and the machine updating can be managed from any device connected to the embosser via Ethernet by using the FTP protocol (file transfer protocol).

USB (type A, type B), Ethernet and WiFi

The **ME1000S** and **ME2000S** can be connected to a personal computer, to load data and start production, or to another device, such as keyboard, barcode reader or other if needed.

With a semi-automatic (**ME1000S**) or automatic (**ME2000S**) loading and unloading are really easy. It is equipped with a unique clamp for plates of different dimensions and materials as well as a large selection of fonts. Once embossed, the metal tags can be placed in an external collection tray via a side eject mechanism or stacked in a FIFO output stacker. It is designed for medium to high volume production process.



Card Solutions For A Better World

SINGAPORE
VICCARD PTE LTD
Tel: +65 6265-2998
Email: viccard@singnet.com.sg
www.viccard.com.sg





MALAYSIA
VICCARD MALAYSIA SDN BHD
Tel: +603 7960-7932
Email: sales@viccard.com.my
www.viccard.com.my



Card Solutions For A Better World


Model ME1000s/2000s Metal Plate Embosser

FEATURES AND SPECIFICATIONS

MODEL NAME	ME1000S - ME2000S
PLATE AND FEEDER	
Dimensions	Rectangular tag: 30 ÷ 115 x 21 ÷ 90 mm - 1.18 ÷ 4.53 x 0.83 ÷ 3.54 in (WxH) Round tag: Ø 38,10 mm - 1.5 in, dog tag: 52 x 29 mm - 2.05 x 1.14 in (WxH) Medical alert tag: 57 x 32 mm - 2.24 x 1.26 in (WxH)
	
rectangular tag	round tag
	
	dog tag
	medical alert tag
Materials	Stainless steel, carbon steel, aluminium, copper and brass
Thickness	0,4 ÷ 0,9 mm - 0.0157 ÷ 0.0354 in
Input hopper	ME1000S: manual feed - Single Access Point ME2000S: up to 250 plates capacity (0,4 mm - 0.0157 in)
Output hopper	ME1000S: manual feed - ME2000S: up to 250 plates capacity Options: FIFO (first in - first out) technology or side eject
MARKING	
Technology	Embossing, Indent or Debossing
Wheel capacity	60 or 90 slots - 45 slots drum available for special applications
Type set	Many character configurations available: Embossing: Simplex 2, OCRB1, Block USA, Double Block, etc. - Height 3 ÷ 12 mm / 0.118 ÷ 0.472 in - Indenting: Simplex1, Simplex 2, etc. Height 1 ÷ 4 mm / 0.039 ÷ 0.157 in - Debossing: Elite Dog Tag
Embossing area	See picture
Performance	231 tags per hour based on 55 characters
COMMUNICATION AND SOFTWARE	
Interface	USB 2.0 port (device and host), Ethernet. WiFi (optional)
Software	Linux based self enclosed software PowerTag PC application proprietary software Windows 7/8/10
Protocol	Multiembosser
Data format	Optional: Cim, Xon-Xoff, Stored Format default, Stored Format Selected and Pound-Pound 50 fields of 42 characters each (Variable, Fixed data, Counters, etc.)
HARDWARE	
System	CPU Arm Cortex-A8 / RAM 256 MB, with flash-disk and file system Linux O.S. based
Power supply	100 - 117 - 220 - 230 or 240 Volts - 50 or 60 Hz
Power consumption	800 Watt max
Operating environment	Temperature: 5 ÷ 40 °C / 41 ÷ 104 °F, relative humidity: 30% ÷ 90% non condensing
VARIOUS	
Others	Built in touch screen 7", multi-language user interface management: English, Spanish, Italian Innovative embedded software up-grade system thru pen drive and web server Machine configuration protected by password for high security and data protection
CERTIFICATIONS	
UL, FCC, CE, ROHS	
WARRANTY	
12 months	




EMBOSSING AREA



Dashed area not usable height
3,5 mm - 0.137 in



DIMENSION



WEIGHT

85,5 Kg / 189 lbs



SOFTWARE

power tag
LITE
optional
power tag
EVO