

# Model ME550 CR80 Metal Tag Embosser















### COMPACT, PORTABLE CR80 METAL TAG EMBOSSER

The **ME550 CR80** is a portable metal tag embosser designed to manage **CR80** tag sizes (85,6 mm x 54 mm / 3.37" x 2.13") ideal for permanent marking of aluminum and stainless steel tags. With a 10% increase in production speed, a completely renewed design and new features, the **ME550 CR80** is an advanced solution that can be integrated into any existing factory or office network.

#### 7" color touchscreen display with high resolution

The **ME550 CR80** is equipped with a built-in 7 "WVGA LCD touchscreen display with simple and easy to use icon and buttons. The user can access and manage machine functions through a multi-level menu in an easy and intuitive way.

#### IoT (Internet of Things) remote access and management

- **Web services:** The machine set-up and operations can be entirely managed remotely via the web or through the use of VNC (Virtual Networking Computing) client, using a personal computer or other devices connected to the Customer's network.
- Data transfer: Data import/export and the machine updating can be managed from any device connected to the embosser via Ethernet by using the FTP protocol (file transfer protocol).

#### USB (type A, type B), Ethernet and WiFi

The **ME550 CR80** can be connected to a personal computer, to load data and start production, or to another device, such as keyboard, barcode reader or other if needed.

The **ME550 CR80** is a completely self-contained tag marking machine, and is ideal for component and production line identification and traceability applications. Designed to operate in harsh industrial environments and easy to transport.



SINGAPORE
VICCARD PTE LTD
Tel: +65 6265-2998
Email: viccard@singnet.com.sg
www.viccard.com.sg

MALAYSIA
VICCARD MALAYSIA SDN BHD
Tel: +603 7960-7932
Email: sales@viccard.com.my
www.viccard.com.my



## Model ME550 CR80 **Metal Tag Embosser**

#### FEATURES AND SPECIFICATIONS

MODEL NAME ME550 CR80

PLATE AND FEEDER

Dimensions Metal plates: CR80 standard 85,6 x 54 mm - 3.37 x 2.13 in (WxH)







Materials Thickness Input hopper Output hopper

Alluminum, stainless steel

Metal plates: 0,356 ÷ 0,70 mm / 0.014 ÷ 0.0275 in Up to 120 plates capacity (0,4 mm / 0.0157 in)

External collection tray

MARKING

Technology Embossing or debossing

Wheel capacity

Type set Simplex 2, Block USA, Block 5, OCRB1

See picture Embossing area

Performance 120 tags per hour based on 55 characters (112 tags per hour based on 60 characters)

**COMMUNICATION AND SOFTWARE** 

USB 2.0 port (device and host), Ethernet. WiFi (optional) Interface Software PowerTag PC application proprietary software compatible with

Windows 8.1/10/11, MacOS (Intel64, da 10.x onwards), Linux

PowerTag USB on USB key for multiple use

Multiembosser Protocol

Optional: Cim, Xon-Xoff, Stored Format default, Stored Format Selected and Pound-Pound

**HARDWARE** 

System CPU Arm Cortex-A8 / RAM 256 MB, with flash-disk and file system Linux O.S. based

Power supply Universal switching power supply 100-240 volts; 50 or 60 hz

Power consumption 300 Watt max

Operating environment Temperature: 5° ÷ 40° c 7 / 41° ÷ 104° F, relative humidity 30% ÷ 90%

**VARIOUS** 

Others Built in touch screen 7", multi-language user interface management: English, Spanish, Italian

Innovative embedded software up-grade system thru pen drive and web server

Interchangeable input hopper for easy charge and discharge of medical alert & dog tags Machine configuration protected by password for high security and data protection

Easy to carry handle, no packaging required

















26 Kg / 57.3 lbs



